


**Everyvalve LTD**  
**ANGLE GLOBE, SWING CHECK, SPRING CHECK Valves**  
 Page 19




**ANGLE GLOBE VALVES (PNEUMATIC) SS & BRZ**

A very useful Pneumatic Control valve for project and general Chemical & process industry applications. Normally Closed is Standard operation wms i.e. (Water, Oil, Aggressive, Media Steam ( 9 Barg Max). Compactness allows easy installation and also spares assy. Plastic actuators also supplied > Type 554 Seals : EPDM :- (Std) Seats:- PTFE, Body :- SS or Bronze Temp Max : 130 Deg C. Pressure Range as shown = (Pr) Type 1 or 2 Metal Actuator>----- ] : [ PP Actuator ]

Type=>M2		ACT 1 (45mm Act)	ACT 1(45mm Act)	ACT 2 (63mm Act)	ACT 2 ( 63mm Act)
		BRONZE	SS316	BRONZE	SS316
Sizes	Pressure (Pr)>	19M1514A	19M1514B	19M2514A	19M2514B
1/2"	16 bar max	£116.82	£ 152.26	-	-
3/4"	16 bar max	£ 128.63	£ 167.81	-	-
1"	16 bar max	£ 161.00	SEE ACT 2 SS316	-	£ 243.15
1.25"	16 bar max	SEE ACT 2 BRONZE	SEE ACT 2 SS316	£ 224.90	£ 293.69
1.5"	12 bar max	SEE ACT 2 BRONZE	SEE ACT 2 SS316	£ 255.98	£ 333.91
2"	8 bar max	SEE ACT 2 BRONZE	SEE ACT 2 SS316	£ 311.53	£ 406.69

Right angled versions are available up 150mm in size (Flanged) Accessories are supplied as extra>- Stroke Limiters, Indicators potentiometric control etc. "554" pressures are 10 Bar over seat. See [page 15](#) for solenoid control valves 15ML377.

**(Wafer Type) SWING CHECK VALVES IN SS 316**




Non return valve for fitting between PN flanges in STEEL pipe- work on a horizontal or vertical plane. Maximum pressure is 16 bars and flows to 4 M / second. Seats are soft FPM with other options of construction. Pulsing service must be avoided. Use bolt torque data shown for "Spring Check Valve". Uses for water, air, chemicals & some acids (SS). Temps to 150°C (Subject to Seals)

Size	Bore	O.D	Thick	Weight	£/Each	
	"C"	"A"	"B"	Kgs	S.S.-	REFERENCE
1.1/2"	24mm	86	15	1	£ 80.00	19M31B15
2"	31mm	97	16	1	£ 82.75	19M31B20
2.5"	37mm	110	16	1	£ 109.75	19M31B25
3"	46mm	129	23	2	£ 122.00	19M31B30
4"	66mm	160	23	4	£ 172.00	19M31B40
5"	91mm	193	23	5	£ 249.25	19M31B50
6"	116mm	216	23	6	£ 324.25	19M31B60
8"	145mm	273	23	14	£ 510.54	19M31B80
10"	191mm	330	30	19	£ 808.25	19M31B81
12"	217mm	380	30	32	£ 1,099.00	19M31B82
14"	263mm	446	43	40	POA	19M31B83
16"	305mm	498	46	51	POA	19M31B84

C.S. Bodied versions are zinc plated + Nitrile seal to BS7773 4360/43a S.S. Bodied versions are in grade 316 + FPM seal. Gunmetal Versions also available (add 10% to SS prices) BS1400) Dual Plate versions = See [page 22](#).

**( WAFER TYPE) SPRING CHECK VALVES IN SS316 & CS**



Non Return Valve for fitting between PN40 flanges in STEEL pipe work only, at any angle. The spring is standard set at 200mm water gauge cracking but other loadings are possible. Max pressure usable is 48 bars & Max temp is 150C. Soft seals are included "FPM". Valve Fits between 4504 BS 10 and 1560 flanges. 37 other body materials available. Applications for water, chemicals & air. Avoid shock use. (Soft FPM seal included)

Size	Metric Bore	Thick.	O.D.	Bolt	Torque.	C.S.		£/Each	
						REFERENCE	£/Each	S.S.	REFERENCE
1/2"	12mm	16mm	x 45	3.5	kg/m	19M400B5	POA	£ 50.00	19M400A05
3/4"	20mm	19mm	x 55	3.5	kg/m	19M400B7	POA	£ 51.75	19M400A05
1"	25mm	22mm	x 65	3.5	kg/m	19M400B10	POA	£ 56.75	19M400A05
1.25"	32mm	28mm	x 76	4.0	kg/m	19M400B12	POA	£ 78.00	19M400A05
1.5"	40mm	32mm	x 86	5.0	kg/m	19M400B15	POA	£ 99.75	19M400A05
2"	50mm	40mm	x 98	6.0	kg/m	19M400B20	POA	£ 127.00	19M400A05
2.5"	65mm	50mm	x 111	6.5	kg/m	19M400B25	POA	Special on request	19M400A05
3"	75mm	50mm	x 130	7.0	kg/m	19M400B30	POA	Special on request	19M400A05
4"	100mm	105mm	x 154	8.0	kg/m	19M400B40	POA	Special on request	19M400A05
6"	160mm	140mm	x 272	8.0	kg/m	19M400B60	POA	Special on request	19M400A05

All information given as a guide only. Suitability must be established before application of products always.

PLEASE NOTE : Prices subject to change without prior notice.