

Pumps : SUBMERSIBLE / CENTRIFUGAL / JET PRESSURE - ******Est. 50 + Year Nocchi Brand******

LIGHT SEWERAGE PUMP (VORTEX) IN SS 304

Application for solids handling to 40mm in sewerage type applications. Not suitable for metal objects/other non stated uses. Max Temp = 50°C Diameter for all = 164mm. Side outlet design

Type BIOX											
Ref	Outlet	Float	Volts	KW	Max l/min	Max Head	Seal	Cable Metre	Wt. Kgs	Tall mm	Price £
25M300/10	2" BSPf	Yes	230vAC	0.75	350	11	Buna	10m	10	410	£506.00
25M400/12	2" BSPf	Yes	230vAC	1.1	450	12	Buna	10m	11	410	£608.00
Type PRIOX											
25M600/13	2" BSPf	Manual	415v3p	1.1	600	13	Buna	10m	12.6	450	£984.00
25M800/18	2" BSPf	Manual	415 v3p	2	800	18	Buna	10m	15	470	£1,068.00



Other larger types are available on special request. Heavier pumps of this type available on special quotation in cast iron.

All flows quoted are related to the head of fluid being pumped. High head means that the flow is greatly reduced & visa-versa Data is based on clean water. Do not run dry. For experienced qualified installation only. Pump should be vertical in operation as all submersible ones of this type. All solids must be less than 40mm to avoid jamming.

CENTRIFUGAL PUMPS IN STAINLESS - BRASS & PPO SS Type (304)

All pumps are flooded suction type working on direct coupled basis. Avoid running dry. Dry running protection recommended. IP 45 connection. Class F Insulation. Continuous Service. 50°C max. Carbon Ceramic Mechanical Seal. Spindle in 416 SS. Impellor made in glass reinforced 'Noryl'. Motor AL) externally ventilated closed type. 'DROPS' system. Closed junction box.

High Pressure Staines Centrifugal Pumps (Multi Stage For Clean Water)

Ref	Inlet	Outlet	Volts AC	KW	L/Min	Head	Imp	Seal	Stage	Wt.Kg	Len mm	Price £
25MCX8036M/T	1" BSPf	1" BSPf	230/415	0.55	80	36m	SS	EPDM	Multi	6	296	£273.00
25MCX8048M/T	1" BSPf	1" BSPf	230/415	0.75	80	46m	SS	EPDM	Multi	7	316	£280.00
25MCX8060M/T	1" BSPf	1" BSPf	230/415	1	80	58m	SS	EPDM	Multi	8	360	£317.00
25MCX12048M/T	1" BSPf	1" BSPf	230/415	1	120	46m	SS	EPDM	Multi	9	316	£328.00
25MCX12060M/T	1" BSPf	1" BSPf	230/415	1.1	120	58m	SS	EPDM	Multi	10	360	£356.00
25MCX20040M/T	1 1/4" BSPf	1 1/4" BSPf	230/415	1.5	200	44m	SS	EPDM	Multi	14	400	£539.00
25MCX20052M/T	1 1/4" BSPf	1 1/4" BSPf	230/415	1.8	200	56m	SS	EPDM	Multi	16	430	£578.00



('M' = Single Phase & 'T' = 3 Phase)

Jet Pumps in SS304 - Single Impeller (Slightly Dirty Water)

Ref	Inlet	Outlet	Volts	KW	L/Min	Head	Imp	Seal	Stage	Wt.Kg	mm	Price £
25M4542 / 43	1" BSPm	1" BSPf	230vAC	0.65	45	43m	SS	EPDM	Single	8	351	£260.00
25M6050M	1" BSPm	1" BSPf	230vAC	0.8	60	50m	SS	EPDM	Single	8.6	351	£276.00
25M9050M	1 1/4" BSPm	1" BSPf	230vAC	1.5	90	50m	SS	EPDM	Single	13	430	£368.00
25M550M With Switch Kit	1" BSPm	1" BSPf	230vAC	0.6	45	42	SS	EPDM	Single	8	240	£182.00



Jet Pumps in PPO

Recommended for potable water. Complete with switch, lead & handle & motor thermal trip. IP 44 insulation Class B winding. Max liquid temp is 50°C. Continuous rating.

Ref	Inlet	Outlet	Volts	KW	L/Min	Head	Imp	Seal	Stage	Wt.Kg	Len mm	Price £
25PURA6042M With Switch Kit	1" BSPm	1" BSPm	230vAC	0.6	40	42m	PPO	EPDM	Single	7	360	£189.00



Brass Type ** Standard Centrifugal Pump **

Ref	Inlet	Outlet	Volts	KW	L/Min	Head	Imp	Seal	Stage	Wt.Kg	Len mm	Price £
25MEP2M/45BR	1" BSPf	1" BSPf	230vAC	0.37	40	40m	BR	Buna	Single	6.2	260	£249.00
25MPB100	1" BSPf	1" BSPf	230vAC	0.7	40	55m	BR	Buna	Single	5	295	£376.00



LW Range Pumps to 22kw available on request in Cast Iron (Separate data) Price on Application

Note figures given are max performances at the end of the scales. Full data is supplied, in the situation of doubt please ask! Grit & dirt will reduce life of pump as will arduous duties. don't run dry.

1" Male BSP Inlet/Outlet Flow Demand Switches.

Ref	25PF15	Price	£94.00
Heavy NEW design pattern. (1.1/4" BSPm & 16 amps rating) works on the opening and closing of a tap in conjunction with a pump. Minimum pressure 2 bar to max of 10 bar. Flow rates 40 to 200 litres/min. Protection for pump also with no flow the pump is not switched on. Indicator lights show the status of operation for full user awareness of a) power on - b) On - signal pump run - c) failure - d) reset. In-line design 0-60°C. Dimensions 165mm L * 170mm W * 230mm H. Engineering polymer body in blue colour. Use on 220v - 240vAC (Adjustable) 2.6/kg (Control Pres)			



Pressure Switch PVC base + PTFE Diaphragm

Ref	25P205	Price	£158.00
Pressure Switch 1/2" BSPm PVC base for chemicals + PTFE Diaphragm 2 - 30 PSI Robust and reliable Enclosure rating IP65 CE Marked Cast Alloy Painted Body Size L : 105 MM W: 70 MM H: 95 MM Weight : 760 Grams			



[Polypropylene Mag Drive Pumps - Click Here For Details](#)

PLEASE NOTE : Prices subject to change without prior notice.

Updated 1/3/2022

Everyvalve Ltd | 19 STATION CLOSE | POTTERS BAR | HERTS | EN6 1TL | TEL : 0044(0)1707642018 | FAX : 0044(0)1707646340 | http://www.everyvalve.com | sales@everyvalve.com

MANUFACTURER AND SUPPLIERS TO COMMERCIAL INDUSTRIES.