









MA3 Electric Barrel and Container Pump		MA5 Electrical Barrel and Container Pump, Seal-Less SL		MP2 Barrel & Container Pump with Air Driven Motor (ex)				
<p>QUANTITY: up to 100 l/min DELIVERY HEAD: Max 8m wg VISCOSITY: Max 300C/poise (mpa.s) approx 40 E TEMPERATURE: Max 50°C(PP) 100°C (alu, SS, PVDF) UNIVERSAL MOTOR 400w, 220v, 110v or 42v with switch MOTOR PROTECTION & 5 meters cable with safety plug PUMP TUBES available in : PP, PVDF, SS316 & aluminium IMMERSION DEPTHS : 700, 900 or 1200 mm Special lengths possible up to 2.5m TUBE OUTSIDE : 40mm Dia (PP) 42mm Dia alu 38mm Dia (SS/HC) WEIGHT: (pump with motor) approx 3.5kg (PP) 7.5kg (SS) PUMP for 220v - VDE + GS</p>		<p>QUANTITY: up to 90 l/min DELIVERY HEAD: Max 20m wg VISCOSITY: Max 460C/poise (mpa.s) approx 60 E TEMPERATURE: Max 50°C(PP) 100°C (alu, SS, PVDF) UNIVERSAL MOTOR 630w, 220v, 115v with switch motor protection & 5 meter cable with safety plug PUMP TUBES available in : PP, PVDF, SS316 & aluminium IMMERSION DEPTHS : 700, 900 or 1200 mm TUBE OUTSIDE : Max 50mm Other sizes as "B3" model WEIGHT: (pump with motor) approx 4.5kg (PP) 8.5kg (SS)</p>		<p>QUANTITY: max 100-200 l/min DELIVERY HEAD: Max 9-18m wc VISCOSITY: Max 3760 C/poise(mpa.s) approx 100 E TEMPERATURE: Max 50°C(PP) 100°C (alu, SS, PVDF) AIR DRIVEN MOTOR with a capacity of approx 300W at 6 bars operating pressure & 6900 rpm AIR CONNECTION: R 3/8 BSP F PUMP TUBES available in :PP, PVDF, SS316 & aluminium IMMERSION DEPTHS : 700, 900 or 1200 mm Special lengths possible up to 2.5m TUBE OUTSIDE : 40/65mm (PP) 55mm alu 38/41/50/55mm Dia (SS) 38mm(HC) WEIGHT: (pump with motor) approx 2.6Kg - 6.5kg ACCESSORIES : airline service equipment - air hose/hose coupling protectors & clips available PUMP for 220v - VDE + GS</p>				
1000mm version (COMPLETE UNIT PRICE BELOW)								
Material	Ref	Price	Material	Ref	Price	Material	Ref	Price
PP	26PMA3PP	P.O.A	PP	26PMA5PP	P.O.A	PP	26PB4DAP	P.O.A
PVDF	26PMA3PV		PVDF	26PMA5PV		PVDF	26PB4DAPV	
S/S	26PMA3SS		S/S	26PMA5SS		S/S	26PB4DASS	
Aluminium	26PMA3AL		Aluminium	26PMA5AL		Aluminium	26PB4DAAL	

Submersible			Submersible			Submersible			Type 205 PP Hand Drum Pump																																																																																											
Waste Pump			SS304 PUMP			High Pressure			Ref: 26P205																																																																																											
Auto	Float down to 50mm	Float Switch down to 50mm	Float Switch down to 50mm	Float Switch down to 50mm	Float Switch down to 70mm				PRICE £49.00																																																																																											
Voltage	240vAC	240 v AC	240 v AC	240 v AC	240 v AC	HIGH OUTPUT:			Dispenses 250ml each down stroke when fully primed																																																																																											
Cable	10 meters + plug	10 meters HO7 RNF + plug	10 meters HO7 RNF + plug	10 meters HO7 RNF + plug	15 meters + plug	CHEMICAL RESISTANT:			Suitable for use with liquid media that is compatible with PP & PTFE (Std. construction materials.)																																																																																											
Outlet	1 1/2" BSPm (Side)	1 1/2" BSPm (Side)	1 1/2" BSPm (Side)	1 1/2" BSPm (Side)	1" BSPm (Side)	CONVENIENT Weight:			1 Kg Stoke is 435mm.																																																																																											
Motor	Oil Double Buna Seal	Oil Double Nitrile Seats	Oil Double Nitrile Seats	Oil Double Nitrile Seats	Oil Double Nitrile Seats	OUTLET: Will align to any angle or direction + optional 20mm Hose Outlet Tail included			VERSATILE : Telescopic uptake PP pipe adjusts to 25/210 litre containers with BSP & Trisure collar adaptor as standard. Free hand use also very useful. Fits all common plastic/metal drums.																																																																																											
Use	Continuous Ambient	Continuous Duty to 45°C	Continuous Duty to 45°C	Continuous Duty to 45°C	Continuous Ambient	FITTING : Don't over tighten the butterfly collar screw or lose 'O' hose tail outlet.			SIZE: Boxed - 520mm * 180mm * 110mm in strong own carton. each complete.																																																																																											
Max	Particles up to 20mm	Particles up to 10mm	Particles up to 10mm	Particles up to 10mm	Clear Water	JS Contractors Heavy Duty Vortex			<table border="1"> <thead> <tr> <th>Ref</th> <th>JS150SVAuto</th> <th>JS250SVAuto</th> <th>JS400SVAuto</th> </tr> </thead> <tbody> <tr> <td></td> <td>26MJ5150SV12</td> <td>26MJ5250SV15</td> <td>26MJ5400SV20</td> </tr> <tr> <td></td> <td>Data Sheet</td> <td>Data Sheet</td> <td>Data Sheet</td> </tr> </tbody> </table>			Ref	JS150SVAuto	JS250SVAuto	JS400SVAuto		26MJ5150SV12	26MJ5250SV15	26MJ5400SV20		Data Sheet	Data Sheet	Data Sheet																																																																													
Ref	JS150SVAuto	JS250SVAuto	JS400SVAuto																																																																																																	
	26MJ5150SV12	26MJ5250SV15	26MJ5400SV20																																																																																																	
	Data Sheet	Data Sheet	Data Sheet																																																																																																	
Omnia Vortex Type	Data Sheet		Dren Standard Type	Data Sheet		Eco High Pressure	Data Sheet		<table border="1"> <thead> <tr> <th>Head (M)XL/M</th> <th>6.5M X 125</th> <th>6.5M X 260</th> <th>7.5M X 260</th> </tr> </thead> <tbody> <tr> <td>Outlet</td> <td>1.1/4"</td> <td>1.1/2"</td> <td>2"</td> </tr> <tr> <td>K.Watts</td> <td>0.15</td> <td>0.25</td> <td>0.4</td> </tr> <tr> <td>Body</td> <td>PP/SS</td> <td>C.I/SS</td> <td>C.I/SS</td> </tr> <tr> <td>HxWxL(M)</td> <td>0.33X0.13X0.18</td> <td>0.4X0.16X0.26</td> <td>0.46X0.16X0.28</td> </tr> <tr> <td>Weight</td> <td>5.5 Kg</td> <td>15kg</td> <td>19Kg</td> </tr> <tr> <td>Solid Size</td> <td><25mm</td> <td><36mm</td> <td><35mm</td> </tr> <tr> <td>Price</td> <td>£209.00</td> <td>£289.00</td> <td>£337.00</td> </tr> </tbody> </table>			Head (M)XL/M	6.5M X 125	6.5M X 260	7.5M X 260	Outlet	1.1/4"	1.1/2"	2"	K.Watts	0.15	0.25	0.4	Body	PP/SS	C.I/SS	C.I/SS	HxWxL(M)	0.33X0.13X0.18	0.4X0.16X0.26	0.46X0.16X0.28	Weight	5.5 Kg	15kg	19Kg	Solid Size	<25mm	<36mm	<35mm	Price	£209.00	£289.00	£337.00																																																									
Head (M)XL/M	6.5M X 125	6.5M X 260	7.5M X 260																																																																																																	
Outlet	1.1/4"	1.1/2"	2"																																																																																																	
K.Watts	0.15	0.25	0.4																																																																																																	
Body	PP/SS	C.I/SS	C.I/SS																																																																																																	
HxWxL(M)	0.33X0.13X0.18	0.4X0.16X0.26	0.46X0.16X0.28																																																																																																	
Weight	5.5 Kg	15kg	19Kg																																																																																																	
Solid Size	<25mm	<36mm	<35mm																																																																																																	
Price	£209.00	£289.00	£337.00																																																																																																	
Omni Pump		Drenox Pump		Eco Diver		JS Contractors Pump			<table border="1"> <thead> <tr> <th>Description</th> <th>Omnia</th> <th>Omnia</th> <th>Omnia</th> <th>Description</th> <th>Dren</th> <th>Dren</th> <th>Dren</th> <th>Eco</th> </tr> </thead> <tbody> <tr> <td>26MOM</td> <td>80/5</td> <td>160/7</td> <td>200/8</td> <td>26MD/26M02</td> <td>80/7</td> <td>160/8</td> <td>250/10</td> <td>350/12</td> <td>90/45</td> </tr> <tr> <td>Head</td> <td>5m</td> <td>7m</td> <td>8m</td> <td>Head</td> <td>7m</td> <td>8m</td> <td>10m</td> <td>12m</td> <td>45m</td> </tr> <tr> <td>L/min</td> <td>80</td> <td>160</td> <td>200</td> <td>L/min</td> <td>80</td> <td>160</td> <td>250</td> <td>350</td> <td>90</td> </tr> <tr> <td>Watts</td> <td>200</td> <td>370</td> <td>550</td> <td>Watts</td> <td>200</td> <td>370</td> <td>550</td> <td>750</td> <td>1100</td> </tr> <tr> <td>Body SS</td> <td>304</td> <td>304</td> <td>304</td> <td>Height</td> <td>231</td> <td>300</td> <td>338</td> <td>338</td> <td>PPO</td> </tr> <tr> <td>Body Dia.</td> <td>177</td> <td>177</td> <td>177</td> <td>Body dia</td> <td>177</td> <td>177</td> <td>177</td> <td>177</td> <td>150</td> </tr> <tr> <td>Weight</td> <td>6kg</td> <td>7kg</td> <td>7kg</td> <td>Weight</td> <td>6kg</td> <td>7kg</td> <td>7kg</td> <td>9kg</td> <td>9kg</td> </tr> <tr> <td>Price</td> <td>£395.00</td> <td>£459.00</td> <td>£533.00</td> <td>Price</td> <td>£381.00</td> <td>£428.00</td> <td>£507.00</td> <td>£594.00</td> <td>£279.00</td> </tr> </tbody> </table>			Description	Omnia	Omnia	Omnia	Description	Dren	Dren	Dren	Eco	26MOM	80/5	160/7	200/8	26MD/26M02	80/7	160/8	250/10	350/12	90/45	Head	5m	7m	8m	Head	7m	8m	10m	12m	45m	L/min	80	160	200	L/min	80	160	250	350	90	Watts	200	370	550	Watts	200	370	550	750	1100	Body SS	304	304	304	Height	231	300	338	338	PPO	Body Dia.	177	177	177	Body dia	177	177	177	177	150	Weight	6kg	7kg	7kg	Weight	6kg	7kg	7kg	9kg	9kg	Price	£395.00	£459.00	£533.00	Price	£381.00	£428.00	£507.00	£594.00	£279.00
Description	Omnia	Omnia	Omnia	Description	Dren	Dren	Dren	Eco																																																																																												
26MOM	80/5	160/7	200/8	26MD/26M02	80/7	160/8	250/10	350/12	90/45																																																																																											
Head	5m	7m	8m	Head	7m	8m	10m	12m	45m																																																																																											
L/min	80	160	200	L/min	80	160	250	350	90																																																																																											
Watts	200	370	550	Watts	200	370	550	750	1100																																																																																											
Body SS	304	304	304	Height	231	300	338	338	PPO																																																																																											
Body Dia.	177	177	177	Body dia	177	177	177	177	150																																																																																											
Weight	6kg	7kg	7kg	Weight	6kg	7kg	7kg	9kg	9kg																																																																																											
Price	£395.00	£459.00	£533.00	Price	£381.00	£428.00	£507.00	£594.00	£279.00																																																																																											
Check 304 usage chemically Max figures given are either one or other. Don't suspend by cable or allow scuffing.									All the above models are with a level float switch for dirty water. All pumps must be services regularly																																																																																											

PP Level Switch (Below) i.e. " Plastic Float fitted with loose 5 m cable. Double Action WRAS Approved						
	Ref	26PG03	Watts	240v * 5 amps max	Use	Water - Fix to side to adjust level Caution with waves
	Price	£48.00	Body	PP Blue 72x153x56mm	Float	Adjust to level
					Cable	5 meters EPDM Rubber