





CHECK VALVE for Sewerage										
	Ref : 06P34240 - 110mm		Approved Check Valve for drainage with mechanical rubber jointed inlet and plain male spigot outlet. Top inspection cover plus lever arm flap control. Cheap valve for easy installation. Terracotta colour. Type 342 / 442.							
	Ref: 06P44260 - 160mm									
	Prices Page 9									
	Size Bore	Body Mat	End Connection socket X spigot	Pres. Rating	Range Temps	Length Body	Seal Materials	Control Function	Volt	Wt. Grms
100mm	PVC	110mm	0.5 Bar	0/40C	270mm	Nitrile	Self Acting	-	1600	-
150mm		160mm			334mm				2800	-
Larger sizes by special request to 500mm for anti-flood use										

Solenoid Direct Operating Valve										
	Ref : 06P52PV02 - PVC		The smallest of chemical solenoid valves with MPM electrical IP65 connectors as standard. Direct action gives good control plus economy of choice. Type 0652							
	Ref : 06P52PF02 - PVDF									
	Prices Page 9									
	Size Orific	Body Material	End Conn.	Pressure Rating	Range Temps	Length Body	Seal Materials	Control Function	Voltages	Wt. Grms
2 mm	PVC	¼" BSP F	0-6 Bar	0/50C	36mm	EPDM or FPM or PTFE	Electric N.C.	240/110AC Rectified 24V DC	210	0.15
4 mm			PVDF		0-3 Bar				36mm	210
6 mm			0-1.5 Bar	0/80C	36mm				210	0.60
For closed circuits there must be a 1 Bar difference between Inlet & Outlet Sockets available on PVC version. Use clean media.										

Solenoid Direct Operating Valve											
	Ref : 06P102		The small + of chemical solenoid valves with MPM electrical IP65 connectors as standard. Direct action gives good control plus economy of choice. For clean chemicals. Type 06102								
	Prices Page 9										
	Size Orific	Body Material	End Connections	Pressure Rating	Range Temps	Length Body	Seal Materials	Control Function	Voltages	Wt. Grms	Max Flow m³ hour
	6 mm	PVC	¼" BSP F	0-6 Bar	0/50C	50mm	EPDM or FPM or PTFE	Electric N.C.	240/110ac Rectified 24 Vdc	480	0.75
8 mm	/	0-3 Bar		/		50mm				480	0.90
10 mm	PVDF	3/8" BSP F	0-1.5 Bar	80C	50mm	480	1.10				
For closed circuits there must be a 1 Bar difference between Inlet & Outlet Sockets available on PVC version. Use clean media.											

Direct Operating Solenoid Valves											
	Ref: 06P105PV		The small ++ of chemical solenoid valves with MPM electrical IP65 connectors as standard. Direct action gives good control plus economy of choice. For Chemicals Clean and dirt free media recommended. Type 06105								
	Prices Page 9										
	Size Orific	Body Material	End Connections	Pressure Rating	Range Temps	Length Body	Seal Materials	Control Function	Voltages	Wt. Grms	Max Flow m³ hour
	6mm	PVC	¼" BSPf or 3/8" BSPf	0 - 6 Bar	0 / 50C	52mm	EPDM or FPM or PTFE	Electric N.C.	240 / 110 AC 24V AC	350	0.90
10mm	PVDF	0 - 1.5Bar									
For closed circuits there must be a 1 Bar difference between Inlet & Outlet Sockets available on PVC version. Use clean media.											